TURN OVER REQUIREMENTS

1. THE CONTRACTOR IS TO ARRANGE FOR ALL INSPECTIONS AND FURNISH THE STORE MANAGER WITH THE CERTIFICATE OF OCCUPANCY. ALSO, PROVIDE A LIST OF NAMES, ADDRESSES, AND TELEPHONE NUMBERS FOR ALL SUBCONTRACTORS, INCLUDING ALL OWNER PROVIDED SUBCONTRACTORS. BOTH ITEMS TO BE MOUNTED IN SEPARATE PICTURE FRAMES (8 1/2" x 11") ON TOILET ROOM PARTITION, ADJACENT TO DOOR AT 5'-0" A.F.F. TO BOTTOM OF FRAME AND ONE COPY OF EACH SHOULD GO TO TENANT'S DIRECTOR OF CONSTRUCTION.

2. PRIOR TO STORE OPENING, THE CONTRACTOR IS TO ARRANGE FOR A CERTIFIED INDEPENDENT BALANCING CONTRACTOR TO BALANCE H.V.A.C. SYSTEM. CONTRACTOR IS TO PROVIDE THE LANDLORD AND TENANT WITH A COPY OF THE BALANCE REPORT.

3. IF REQUIRED BY LANDLORD, CONTRACTOR SHALL SECURE THE NECESSARY APPROVAL OF STORES SPRINKLER SYSTEM FROM LANDLORD'S FIRE INSURANCE CARRIER.

4. TURN OVER ALL KEYS TO STORE MANAGER CLEARLY MARKING EACH KEY FOR

IDENTIFICATION.

6. INSTALL REMAINING OWNER SUPPLIED FIXTURES AND HARDWARE ARRIVING ON MERCHANDISE TRUCK.

5. EXPLAIN OPERATION OF ALL MECHANICAL SYSTEMS TO STORE MANAGER.

7. GENERAL CONTRACTOR IS RESPONSIBLE TO PROVIDE TRASH CONTAINER FOR ALL INITIAL MERCHANDISE PACKING PRIOR TO STORE OPENING.

8. G.C. SHALL REMOVE ALL EXCESS BUILDING MATERIALS FROM SITE PRIOR TO STORE OPENING.

GENERAL CEILING NOTES

1. COORDINATE THE WORK OF ALL TRADES INVOLVED IN THE CEILING WORK TO INSURE CLEARANCES FOR FIXTURES, DUCTS, PIPING, CEILING SUSPENSIONS SYSTEM, ETC. NECESSARY TO MAINTAIN THE FINISHED CEILING HEIGHTS INDICATED ON ARCHITECT'S

2. PROVIDE CEILING ACCESS PANELS AS REQUIRED FOR EQUIPMENT AND SYSTEM MAINTENANCE, AND MATCH ADJACENT CEILING FINISH U.O.N.

3. ALL SOFFITS AND CEILING HEIGHTS ARE DIMENSIONED FROM TOP OF FINISHED FLOOR TO BOTTOM OF FINISHED DRYWALL AND SHALL ALLOW FOR THICKNESS OF ALL FLOOR FINISHES.

4. NOTIFY TENANT OF ANY CONFLICTS OF LIGHT FIXTURE LOCATIONS WITH MAIN RUNNERS, DUCTS, STRUCTURE, HVAC, AND/OR (E) CONDUIT, PRIOR TO FRAMING FOR LIGHTS. ANY DISCREPANCIES BETWEEN ARCHITECT'S CEILING LOCATIONS AND ACTUAL FIELD CONDITIONS ARE TO BE CLARIFIED WITH THE TENANT PRIOR TO FRAMING.

5. VERIFY FIELD CONDITIONS AND LOCATIONS OF ALL PLUMBING, MECHANICAL DUCTS, STRUCTURAL ELEMENTS AND ANY AND ALL OTHER APPLICABLE ITEMS. INSTALL APPLICABLE NEW PLUMBING, MECHANICAL FANS, DUCTS, CONDUITS, AND OTHER RELATED AND APPURTENANT ITEMS SO AS NOT TO CONFLICT WITH LUMINARIES AND ANY AND ALL FIELD CONDITIONS.

6. INSTALL LIGHT FIXTURES WITH PROTECTIVE FILM OR SIMILAR COVER OVER LOUVER, LENS, BAFFLE, AND THE LIKE, TO AVOID FIXTURE OILING OR DAMAGE, FIXTURES SHALL BE MAINTAINED CLEAN AND AS NEW. LAMPS SHALL BE NEW AT PROJECT COMPLETION.

7. INSTALL THE SUSPENDED CEILING ACCORDING TO THE RECOMMENDATIONS OF THE CEILING SYSTEM MANUFACTURER.

8. CONTRACTOR SHALL PROVIDE ALL LATERAL BRACING, COMPRESSION STRUTS AND HOLD-DOWN CLIPS, AS REQUIRED BY THE GOVERNING JURISDICTION, FOR ALL SUSPENDED CEILING AND SOFFIT FRAMING CONDITIONS.

9. VERIFY ABILITY OF EXISTING STRUCTURE ABOVE TO SUPPORT THE NEW SUSPENDED CEILING SYSTEM AND INCLUDED EQUIPMENT.

10. INSTALL ADDITIONAL BACKING PLATES/BLOCKING AND SUSPENSION WIRES AT ALL EQUIPMENT ATTACHED DIRECTLY TO THE NEW SUSPENDED CEILING SYSTEM AND NOT INDIVIDUALLY SUPPORTED OTHERWISE.

GENERAL NOTES

1. NO WORK DEFECTIVE IN WORKMANSHIP OR QUALITY OR DEFICIENT IN ANY REQUIREMENTS OF THE CONTRACT DOCUMENTS WILL BE ACCEPTABLE DESPITE THE ARCHITECT'S/TENANT'S FAILURE TO DISCOVER OR POINT OUT DEFECTS OR DEFICIENCIES DURING CONSTRUCTION. DEFECTIVE WORK REVEALED WITHIN THE TIME REQUIRED BY GUARANTEE SHALL BE REPLACED BY WORK CONFORMING TO THE INTENT OF THE CONTRACT. NO PAYMENT, EITHER PARTIAL OR FINAL, SHALL BE CONSTRUED AS AN ACCEPTANCE OF DEFECTIVE WORK OR IMPROPER MATERIALS.

2. SHOULD ANY PORTION OF THE CONTRACT DOCUMENTS PROVE TO BE FOR WHATEVER REASON UNENFORCEABLE, SUCH UNENFORCEABILITY SHALL NOT EXTEND TO THE REMAINDER OF THE CONTRACT NOR SHALL IT VOID ANY OTHER PROVISIONS OF THE CONTRACT.

3. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE DISTRIBUTION OF DRAWINGS TO ALL TRADES UNDER HIS JURISDICTION.

4. DO NOT PROCEED WITH ANY WORK REQUIRING ADDITIONAL COMPENSATION BEYOND THE CONTRACT AMOUNT WITHOUT WRITTEN AUTHORIZATION FROM THE TENANT, FAILURE TO OBTAIN AUTHORIZATION SHALL INVALIDATE ANY CLAIM FOR EXTRA COMPENSATION.

5. ALL INSTALLED PLUMBING, MECHANICAL, AND ELECTRICAL EQUIPMENT SHALL OPERATE QUIETLY AND FREE OF VIBRATION.

6. UPON NOTIFICATION OF COMPLETION OF THE WORK AND DELIVERY OF THE CONTRACTOR'S PUNCH-LIST THE TENANT SHALL PREPARE A PUNCH-LIST OF CORRECTIONS, UNSATISFACTORY AND/OR INCOMPLETE WORK. FINAL PAYMENT WILL BE CONTINGENT UPON THE COMPLETION OF THESE ITEMS UNDER THE TERMS OF THE OWNER/CONTRACTOR AGREEMENT.

7. ALL MATERIALS SHALL BE NEW, UNUSED, AND OF THE HIGHEST QUALITY IN EVERY RESPECT UNLESS OTHERWISE NOTED, MANUFACTURED MATERIALS AND EQUIPMENT SHALL BE INSTALLED AS PER MANUFACTURER'S RECOMMENDATIONS AND INSTRUCTIONS U.O.N.

8. COORDINATE ALL WORK WITH BUILDING OWNER SO AS NOT TO DISTURB OR CAUSE DAMAGE TO ANY TENANT IN THE BUILDING. AVOID CONFLICT AND INTERFERENCE WITH NORMAL BUILDING OPERATIONS BY COMPLYING WITH THE BUILDING'S REGULATIONS REGARDING SCHEDULING AND USE OF ELEVATORS AND LOADING DOCKS FOR DELIVERIES, HANDLING OF MATERIALS, EQUIPMENT, AND DEBRIS.

9. PROVIDE PROTECTION TO ALL EXISTING FINISHES IN ALL SPACES WITHIN OR ADJACENT TO THE SCOPE OR WORK AND THE TENANT'S SPACE. THE CONTRACTOR SHALL PATCH AND REPAIR ANY DAMAGE CAUSED BY HIM OR HIS SUBCONTRACTORS. REFINISH TO MATCH EXISTING ADJACENT FINISH, OR AS NOTED HEREIN.

10. ALL ON-SITE MATERIAL STORAGE SHALL BE INSIDE THE DEMISED PREMISES.

11. CORRECT ANY DEFECTS FOUND IN EXISTING BUILDING CONSTRUCTION WHICH AFFECT THE SCOPE OF WORK THIS INCLUDES BUT IS NOT LIMITED TO UNEVEN SURFACES AND FINISHES AT DRYWALL OR DAMAGED FIREPROOFING. PATCH AND REPAIR SURFACES TO MATCH ADJACENT, ADJOINING SURFACES.

12. THE ARCHITECT/TENANT HAS NO KNOWLEDGE OF AND SHALL NOT BE HELD LIABLE FOR ANY ASBESTOS OR OTHER HAZARDOUS MATERIALS ON THE JOB SITE IF ASBESTOS OR OTHER HAZARDOUS MATERIALS ARE DISCOVERED DURING CONSTRUCTION OR DEMOLITION, STOP WORK AND CONTACT TENANT FOR FURTHER INSTRUCTIONS BEFORE PROCEEDING.

13. ALL REQUIRED EXITS SHALL BE OPERABLE FROM INSIDE, WITHOUT THE USE OF KEY OR SPECIAL KNOWLEDGE.

14. EXIT DOORS AT STOREFRONT TO HAVE SIGN ON TOP RAIL STATING "THIS DOOR TO REMAIN UNLOCKED DURING BUSINESS HOURS" IN 1" HIGH WHITE LETTERS ON A TRANSPARENT BACKGROUND. LOCKING DEVICE TO BE OF THE TYPE THAT IS READILY DISTINGUISHABLE AS LOCKED.

GENERAL NOTES (CONT'D)

15. ALL ROOF DECK PENETRATIONS AND EXTERIOR WALL OPENINGS SHALL BE GUARANTEED BY THE CONTRACTOR TO BE WATERTIGHT FOR A MINIMUM PERIOD OF ONE YEAR AFTER SUBSTANTIAL COMPLETION OF ALL WORK UNDER THIS CONTRACT.

16. SEALANT, CAULKING AND FLASHING, ETC. LOCATIONS SHOWN ON DRAWINGS ARE NOT INTENDED TO BE INCLUSIVE. FOLLOW MANUFACTURER'S INSTALLATION RECOMMENDATIONS AND STANDARD INDUSTRY AND BUILDING PRACTICES.

17. ALL CONCEALED SPACES CREATED BY FURRING BEHIND BUILT-IN CASE WORK AND PANELING SHALL HAVE FIRE BLOCKING (MINERAL FIBER OR APPROVED ALTERNATE) SO THAT NO VOID EXCEEDS 10' VERTICALLY OR HORIZONTALLY.

18. FIRE BLOCKING SHALL BE INSTALLED IN CONCEALED SPACES FORMED BY FLOOR SLEEPERS IN AREAS OF NOT MORE THAN 100 SQUARE FEET.

19. ALL BUILT-IN CASES AND PANELING SHALL MEET A MINIMUM CLASS III FLAME SPREAD (76-200 FLAME SPREAD INDEX). PLYWOOD SHALL BE STAMPED WITH UL LABEL.

20. CONTRACTOR SHALL LEAVE PREMISES AND ALL AFFECTED AREAS CLEAN AND NORDERLY, READY FOR OCCUPANCY. THIS INCLUDES CLEANING OF ALL GLASS (INSIDE AND OUTSIDE) AND FRAMES, BOTH NEW AND EXISTING.

21. ALL WORK SHALL BE PERFORMED IN A PROFESSIONAL, WORKMANLIKE MANNER AND SHALL CONFORM TO ALL STATE, FEDERAL, AND LOCAL CODES. INDUSTRY ORGANIZATION STANDARDS, OR AS REQUIRED BY LANDLORD. OTHERWISE CONTRACTOR WILL BE HELD LIABLE TO CORRECT ANY MISTAKES NOT COMPLYING TO THESE CODES AND ORGANIZATIONS AS MENTIONED.

22. REFER TO SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS. ONE COMPLETE COPY OF THE CURRENT SPECIFICATIONS AND ALL ADDENDA MUST BE KEPT AT THE JOB AT ALL TIMES. NO EXTRAS OR EXTENSIONS WILL BE GRANTED FOR FAILURE TO FOLLOW THE

23. AS A GENERAL RULE, DIMENSIONS ARE TAKEN FROM MAJOR SURFACES OR PANEL SURFACES, NOT FROM THE PROJECTIONS OF MOLDINGS APPLIED TO THE SURFACE OR EDGE. MOLDING PROJECTIONS VARY, BUT MOST ARE 1/4" TO 3/8" BEYOND THE FACE.

24. ALL BLOCKING ABOVE CEILING OR IN PARTITIONS SHALL BE 'NONCOMBUSTIBLE' APPLY 'FLAMORT' FIRE RETARDANT COATINGS WHERE NECESSARY TO MEET CODES OR LANDLORD REQUIREMENTS - SEE SPECIFICATIONS.

25. This contractor shall maintain all fire ratings as required by codes. By the landlord an his fire underwriter.

26. STRUCTURAL FRAMING MEMBERS FOR THE STOREFRONT AND INTERIOR AREAS SHALL BE LOAD BEARING STUDS. THIS CONTRACTOR SHALL COORDINATE WITH THE LANDLORD ON LOCATIONS, WEIGHT, AND METHOD OF ATTACHMENT OF ALL LOADS IMPOSED ON THE OVERHEAD STRUCTURE. ANY FIREPROOFING THAT IS DISTURBED SHALL BE RESTORED TO ITS ORIGINAL CONDITION.

27. ALL NAIL, SCREW, AND FASTENER HOLES SHALL BE FILLED AND SANDED SMOOTH, READY FOR PAINTING JOINTS IN MATERIAL SHALL BE KEPT TO A MINIMUM AND SHALL BE AT CORNERS WHEN POSSIBLE JOINTS IN EXPOSED FACES SHALL BE TIGHT AND FLUSH JOINTS SHOULD BE PLANNED TO FALL BEHIND MOLDING. ALL EXPOSED JOINTS SHALL BE FILLED AND SANDED.

28. ALL OUTSIDE CORNERS WHICH ARE VISIBLE AND ARE NOT COVERED BY MOLDINGS. SHALL BE MITERED, TRUE AND TIGHT, EXPOSED EDGES OF PLYWOOD SHALL NOT BE

29. THIS CONTRACTOR SHALL COORDINATE ALL WORK ON THE SIGN AND SIGN LIGHTING WITH E.C. AND TENANT. THE SIGN WILL BE FURNISHED BY TENANT, SAFE HANDLING, STORAGE AND INSTALLATION SHALL BE THE RESPONSIBILITY OF THE G.C. REPAIR OF ANY DAMAGE TO THE SIGN. WILL BE UNDER THE DIRECTION OF TENANT AT THE G.C.'S EXPENSE.

30. THE G.C. SHALL COORDINATE THE PAINTING OF THE LIGHTING FIXTURES AND OTHER SPECIAL EQUIPMENT DETAILED IN THE FINISH SCHEDULE SEE ALL SPECS.

31. THIS CONTRACTOR SHALL COORDINATE WITH THE LANDLORD (AND OTHERS AS REQ'D.) FOR THE ERECTION OF BARRICADES, MOVEMENT OF MATERIALS, TRASH REMOVAL.

32. TENANT SHALL FURNISH WOOD FLOORING, SIGN, LIGHT FIXTURES, DECALS, DETEX ALARM, SLOTTED STANDARD IN METAL STUD ASSEMBLY AND MILLWORK PACKAGE ALL OF WHICH ARE TO BE INSTALLED BY THE CONTRACTOR.

33. THIS CONTRACTOR SHALL PROVIDE ADEQUATE PROTECTION FOR ALL FINISHED FLOORS DURING CONSTRUCTION, IN PARTICULAR ALL FLOORS SHALL BE PROTECTED AS FOLLOWS PRIOR TO THE ARRIVAL OF STORE FIXTURES, WOOD FLOORS SHALL BE COVERED COMPLETELY WITH 70 LB. KRAFT PAPER. CARPET SHALL BE COVERED WITH 4 MIL VISQUEEN CERAMIC TILE SHALL BE COVERED WITH 1/4" PLYWOOD.

34. TENANT SHALL FURNISH, PRIOR TO OPENING, ABC TYPE FIRE EXTINGUISHERS OF SIZE REQUIRED BY LOCAL CODES.

35. IF APPLICABLE, THE GENERAL CONTRACTOR SHALL COORDINATE WITH THE MECHANICAL CONTRACTOR AND THE LANDLORD THE LOCATION AND SIZE OF RETURN AIR OPENINGS IN THE DEMISING WALLS ABOVE THE CEILING THIS CONTRACTOR SHALL PROVIDE A REAMING SECURITY SCREEN OVER THESE OPENINGS OF 1"x1" WIRE MESH.

36. THE GENERAL CONTRACTOR SHALL FIELD MEASURE THE LEASED PREMISES AND PROVIDE TENANT A DRAWING WITH ACCURATE ACTUAL DIMENSIONS, PARTICULARLY VERIFY DIMENSIONS IN THE AREA OF THE STOREFRONT. NOTIFY TENANT OF ANY DISCREPANCIES AND PROBLEMS THAT MAY OCCUR IMMEDIATELY.

37. THIS CONTRACTOR SHALL PROVIDE EXPANSION JOINTS IN THE HARDWOOD FLOOR STOREFRONT, WALLS ETC. AS SHOWN OR REQUIRED EXPANSION JOINT IN HARDWOOD FLOOR SHALL BE THE RUBBER OR NEOPRENE TYPE, SET FLUSH WITH THE HARDWOOD FLOOR IN EITHER SIDE.

38. FURRING CHANNELS SHALL BE GALVANIZED, METAL STUDS SHALL BE 20 GAUGE MIN. GALVANIZED STEEL WITH MATCHING TRACKS IN WIDTHS AS SHOWN ON THESE DRAWINGS. USE MINIMUM 20 GAUGE (OR AS INDICATED) LOAD BEARING METAL STUDS WHERE INDICATED. METAL 'C' JOISTS SHALL BE 14 GAUGE WITH APPROPRIATE CONNECTORS AND FASTENERS. WELD CONNECTIONS AS INDICATED OR REQUIRED

39. IF EXISTING G.C. SHALL REPAIR ANY FIRE PROOFING ON EXISTING STRUCTURAL STEEL MEMBERS WHETHER IT BE SPRAY-ON OR OTHER.

40. PRIOR TO BID SUBMISSION AND COMMENCEMENT OF WORK, THE G.C. SHALL MAKE A SITE VISIT TO THE EXISTING SPACE TO REVIEW DEMOLITION/SALVAGE REQUIREMENTS. COORDINATE ALL DEMOLITION WITH TENANT'S MANAGER OF CONSTRUCTION AND LANDLORD'S FIELD REPRESENTATIVE.

41. NOTHING SHALL BE ATTACHED TO OR SUSPENDED FROM ROOF DECK ABOVE. G.C. SHALL BRACE/SECURE FROM TOP CHORD OF JOIST OR STRUCTURAL STEEL ONLY.

DEFINITIONS

TENANT - AMERICAN EAGLE OUTFITTERS, INC. G.C. - GENERAL CONTRACTOR LANDLORD - MALL'S LANDLORD

NOTE:

THE USE OF CONTRACTORS

SHALL BE DICTATED BY THE

TERMS AND CONDITIONS OF

THE LEASE AGREEMENT.

T	KESI				RNISHE				Y SCHEDULE
		Y Idd√ T	[
		ת ה ה	STING	NAN	LANDLORD	VAN	NDLORI		
	DESCRIPTION GENERAL REQUIREMENTS	2	3 2	1 1	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Σ μ	! <u>₹</u>	9.0	REMARKS
	BARRICADE CLEAN UP			•		•		•	
	CONSTRUCTION GRAPHICS INSPECTION / COORDINATION						Ŀ	•	
	INSURANCE JOB PHONE						H		
ŀ	PERMITS AND FEES STORE PHOTOS TEMPORARY ELECTRIC				9		F		SEE NOTE THIS SHEET
	TEMPORARY ENCLOSURE TEMPORARY HEAT	+		F			F	•	INCLUDES NOISE / DUST PROTECTION
	SITE WORK	+		F			F		
_	CORE DRILL/TRENCH SLAB DEMOLITION	+		F			F		
	SIDEWALK MISC. SITE WORK	•		F			F		
	CONCRETE SLAB			Е			Е		
L	CONCRETE REINFORCEMENT CONCRETE SLAB		•				L		
	CONCRETE SLAB REPAIR EXPANSION JOINT MATERIAL	•		E			E	•	
	MISC. CONCRETE WORK			E	-		E		SAW CUTS AS REQUIRED, BY G.C.
	MASONRY BRICK CONCRETE BLOCK			•			F	•	BRICK VENEER (IF APPLICABLE) INCLUDES DEMISING WALL REPAIR
ŀ	PLASTER QUARTZITE			0			F	•	PLASTER FINISH (IF APPLICABLE)
	STONE TILE	#		•			F	000	STONE VENEER (IF APPLICABLE) COMMERCIAL GRADE CERAMIC TILE AT TOILET ROOM BY G.C.
	MISC. MASONRY WORK	+		Í			F		TO THE STATE SERVING THE AT TOTAL ROUTED G.C.
	METALS FRAMING FOR DRYWALL CEILINGS/SOFFITS	+					F	•	
	METAL FIXTURES / ACCESSORIES METAL STUDS	1		•			E	•	
	DEMISING PARTITIONS FURRING	\pm	Ŧ	F	•		•	•	METAL STUDS ONLY, IF NOT EXISTING
	INTERIOR PARTITIONS ROOF TOP FRAMING FOR HVAC	•		E		1	F	•	
	STOREFRONT FRAMING STRUCTURAL STEEL	•		É				•	
	SUSPENDED CEILING GRID SYSTEM MISC. STRUCTURAL FRAMING/METAL	‡					Ė	•	
	CARPENTRY PLOCKING (F.D.T. AC. RECHIRED)	#					E		MAINTINA MAINTINA PROPERTY AND
	BLOCKING (F.R.T. AS REQUIRED) PLYWOOD (F.R.T. AS REQUIRED)	\pm					E		MOUNTING NAILERS FURNISHED BY TENANT PLYWOOD AT STOREAGE DECK FURNISHED BY TENANT
	PREFABRICATED FITTING ROOM PARTITIONS PREFABRICATED MILLWORK COMPONENTS	#		•			_	<u> </u>	
	MISC. CARPENTRY			E	•		E		
	THERMAL / MOISTURE PROTECTION CAULKING INSULATION	+		E	9		_	•	
	SEALANTS VAPOR BARRIER(S)			F			F		
	WATERPROOFING MISC. THERMAL / MOISTURE PROTECTION	+		F					
	DOORS	+		F			F		
	ENTRY DOOR / GRILLE STOCK ROOM DOOR			•	_		F	<u>•</u>	TO MATCH MALL STANDARD
ľ	TOILET ROOM DOOR SERVICE DOOR	+		0	_	ı	F	0	
	FITTING ROOM DOOR DOOR HARDWARE			0			F	<u>•</u>	
 和				H			H		
	BASE BRICK / STONE			•			Ŀ	•	
	METAL BASE			•			Ŀ	•	
	VINYL COVE WOOD BASE \$ SHOE			•		2	L	<u>•</u>	
	ACOUSTIC TILE	+					_	•	
	PAINT WOOD PLANKS / CELLING BEAMS							•	
	WOOD PLANKS / CEILING BEAMS FLOOR CARPETING							•	
	CARPETING CERAMIC / PORCELAIN TILE CONCRETE	+		ě					
	HARDWOOD FLOORING LAMINATE FLOORING	+		•	_	•			COORDINATED BY G.C.
	MALL TILE / FLOORING RESILIENT VINYL FLOORING	+		ŕ				•	
	TRANSITION STRIP TRAVERTINE / STONE TILE	+		•			_		
_	WALLS BRICK / STONE	+		•			F	•	
	CERAMIC / PORCELAIN TILE FABRIC COVERINGS	\pm		0			F	•	COMMERCIAL GRADE CERAMIC TILE AT TOILET ROOM
	GYPSUM BOARD METAL PANELS			•			E	•	
	PAINT WALL PAPER / SPECIAL GRAPHICS	f		•			_	0	
	WOOD PLANKS / MILLWORK PANELS	<u> </u>		•					
	SPECIALTIES & EQUIPMENT AUDIO / VIDEO SYSTEM	+		•		•			COORDINATE LOCATIONS WITH FIRE MARGHAL
	FIRE EXTINGUISHERS (2A10BC) MIRROR GLASS (MILLWORK COMPONENTS) MIRROR GLASS (FIXTURE COMPONENTS)	#		•				•	COORDINATE LOCATIONS WITH FIRE MARSHAL
	FAUX & DISPLAY CASE GLASS SIGNAGE	‡		•				•	SUPPLIED BY MILLWORK SUPPLIER SUPPLIED BY SIGN CONSULTANT
	STOREFRONT ALUMINUM STOREFRONT SYSTEM	+							(IF APPLICABLE)
	STOREFRONT GLASS ALUMINUM GLAZING CHANNEL	+	0			1	F		
	GLASS CLAMPS STOREFRONT MATERIALS/FINISHES	+		•			_	9	
	WINDOW DECALS TOILET ROOM ACCESSORIES						F		IF REQUIRED: FURN. BY TENANT, INST. BY G.C.
	TRANSOM GLASS @ DOOR OPENINGS FURNISHINGS	}		•					
	STOCK ROOM SHELVING MILLWORK FIXTURES / FURNITURE	#		•			F	•	
	MISC. FURNITURE	1		•			F	•	
	MECHANICAL REFER TO MECHANICAL DOCUMENTS FOR RES	PON	ISIE	I BILIT	TY IN	NFO	RMA	ATIO	ON
	ELECTRICAL	Ι							
	REFER TO ELECTRICAL DOCUMENTS FOR RES	ON!	SIB	ILIT I	YIN	IFOF	RMÁ I	TIC	2N
	TOILET ROOM FIXTURES REFER TO TOILET ROOM DETAILS ('A.O.150' D	RAV	NIN	G S	ERIE	s)	FOF	2 R	RESPONSIBILITY INFORMATION
	PREFABRICATED LIGHT BOX (WHERE OCCURS) LIGHT BOX	+							SUPPLIED AND INSTALLED BY SIGN CONSULTANT
	MILLWORK FIXTURES / SURROUND	#		ĕ				•	SOLLED AND INSTALLED DI SIGN CONSULTANT
		Į.				-			_

الح **₩** (C \mathbf{C} NER SPO

tore No.

Drawing No.

IA 0.01