

AMERICAN EAGLE FINISH & MATERIAL LEGEND

NOTE:
NOT ALL FINISHES SHOWN ON THIS SHEET
ARE REQUIRED. SEE ARCHITECTURAL
DRAWINGS FOR FINISHES USED.

WOOD FINISHES

TYPE	DESCRIPTION	LOCATION	PROFILE	FLAME SPREAD
[WD-1a]	3/4" [19] THICK, SOLID STOCK #2 COMMON PAINT GRADE YELLOW POPLAR AT WOOD DESIGNATED TO BE PAINTED, TIGHT KNOTS AND CHECKING DESIRABLE, SURFACED 2 SIDES, UNSANDED	ENTIRE STORE (SIZES & CONFIGURATIONS VARY)		CLASS C FLAMESPREAD (175)
[WD-2a]	5/8" [16] - MEDIUM DENSITY FIBERBOARD (MDF) PREPRIMED. PREROUTED 1/8" [3] X 1/8" [3] D SLOTS AT 4" [102] O.C.	WALL PANELS, MILLWORK, DISPLAY CASES AS INDICATED		CLASS C FLAMESPREAD (120)
[WD-3a]	5/8" [16] - MEDIUM DENSITY FIBERBOARD (MDF) PREPRIMED.	MILLWORK, TRANSOM DISPLAY CASES		CLASS C FLAMESPREAD (120)
[WD-4a]	5/8" [16] 'ARCHITECTURAL GRADE' (WHITE OAK VENEERED) MEDIUM DENSITY FIBERBOARD (MDF) PREROUTED 1/8" [3] X 1/8" [3] D SLOTS AT 4" [102] O.C. (BY MILLWORK SUPPLIER) (FIELD CUT AS REQUIRED)	FAUX & DISPLAY CASES (STAINED)		CLASS C FLAMESPREAD (120)
[WD-5a]	3/4" [19] THICK, SOLID STOCK WHITE OAK, TIGHT KNOTS AND CHECKING DESIRABLE, SURFACED 2 SIDES, SANDED	FAUX & DISPLAY CASES (STAINED)		CLASS C FLAMESPREAD (100)
[WD-6a]	1/2" [13] 'ARCHITECTURAL GRADE' (HICKORY VENEERED) MEDIUM DENSITY FIBERBOARD (MDF) 6" [152] PLANKS WITH 1/16" [2] GROOVES (BY MILLWORK SUPPLIER) (FIELD CUT AS REQUIRED)	WALL PANEL, VESTIBULE, PASSAGE, FITTING ROOMS		CLASS C FLAMESPREAD (120)
[WD-7a]	VENEERED LAMINATE CEILING SYSTEM (B) [127] 6mm ECO CLIQUE FLAT WHITE #7 (SHEEN) (PREFINISHED) INSTALLED OVER 5/8" DRYWALL. FURNISHED BY TENANT, INSTALLED BY G.C., G.C. SHALL COORDINATE.	SELECT SALES AREA CEILING		ASTM E 648 CLASS A FLAMESPREAD
[WD-8a]	5/8" [16] (HICKORY VENEERED) PLYWOOD BY MILLWORK SUPPLIER (FIELD CUT AS REQUIRED)	ENTRY PORTAL (STAINED)		CLASS C FLAMESPREAD (175)
[WD-9a]	3/4" [19] THICK, SOLID STOCK HICKORY, TIGHT KNOTS DESIRABLE, SURFACED 4 SIDES, SANDED	ENTRY PORTAL, STAINED		CLASS C FLAMESPREAD (120)
[WD-10a]	5/8" [16] MEDIUM DENSITY FIBERBOARD (MDF). 8" [203] WIDTH BOARDS WITH 1/8" [3] GROOVES. PREPRIMED.	HORIZONTAL STOREFRONT APPLICATION		CLASS C FLAMESPREAD (120)
[WD-11a]	1/2" [13] 'ARCHITECTURAL GRADE' (HICKORY VENEERED) MEDIUM DENSITY FIBERBOARD (MDF) 8" [203] PLANKS WITH 1/16" [2] GROOVES BY MILLWORK SUPPLIER (FIELD CUT AS REQUIRED)	STOREFRONT		CLASS C FLAMESPREAD (120)
[WD-12a]	3/4" [19] MEDIUM DENSITY FIBERBOARD (MDF) PREPRIMED.	INTERIOR CEILING TRIM (SIZES & CONFIGURATIONS VARY)		CLASS C FLAMESPREAD (120)
[WD-13a]	1/4" [6] 'ARCHITECTURAL GRADE' (HICKORY VENEERED) PLYWOOD (MDF) BY MILLWORK SUPPLIER.	LIGHT BAR		CLASS C FLAMESPREAD (120)
[WD-14a]	5/8" [16] SOLID STOCK WHITE OAK, SURFACED 1 SIDE. 8" [203] WIDTH BOARDS WITH 1/8" [3] GROOVES. PREPRIMED.	HORIZONTAL STOREFRONT APPLICATION		CLASS C FLAMESPREAD (120)
[WD-15a]	5/8" [16] 'EXTERIOR GRADE' (WHITE OAK VENEERED) PLYWOOD BY MILLWORK SUPPLIER (FIELD CUT AS REQUIRED)	ENTRY PORTAL (STAINED)		CLASS C FLAMESPREAD (175)
[WD-16a]	3/4" [19] THICK, SOLID STOCK WHITE OAK, TIGHT KNOTS DESIRABLE, SURFACED 4 SIDES, SANDED	ENTRY PORTAL, STAINED		CLASS C FLAMESPREAD (120)
[WD-17a]	3/8" [10] THICK SHIPLAP PLANKS, SOLID STOCK #2 COMMON PAINT GRADE YELLOW POPLAR TIGHT KNOTS AND CHECKING DESIRABLE.	STOREFRONT, VESTIBULE, PASSAGE		CLASS C FLAMESPREAD (175)
[WD-18a]	5/8" [16] 'ARCHITECTURAL GRADE' MEDIUM DENSITY FIBERBOARD (MDF) PREPRIMED WITH PREMACHINED 'BEADBOARD' LOOK BY MILLWORK SUPPLIER. (FIELD CUT AS REQUIRED)	SALES AREA DISPLAY CASES AS INDICATED		CLASS C FLAMESPREAD (120)
[WD-19a]	SOLID STOCK WESTERN RED CEDAR TIGHT KNOTS AND CHECKING DESIRABLE, SURFACED 2 SIDES, UNSANDED.	EXTERIOR STOREFRONT TRIM (SIZES & CONFIGURATIONS VARY)		CLASS B FLAMESPREAD (70)
[WD-20a]	3/8" [10] THICK SHIPLAP PLANKS, SOLID STOCK WESTERN RED CEDAR, TIGHT KNOTS AND CHECKING DESIRABLE.	EXTERIOR STOREFRONT		CLASS B FLAMESPREAD (70)
[WD-21a]	5/8" [16] - MEDIUM DENSITY FIBERBOARD (MDF) PREPRIMED. PREROUTED 1/8" [3] X 1/8" [3] D SLOTS AT 6" [152] O.C.	FAUX & DISPLAY CASES		CLASS C FLAMESPREAD (120)
[WD-22a]	3/4" [19] THICK SHIPLAP PLANKS, SOLID STOCK #2 COMMON PAINT GRADE YELLOW POPLAR TIGHT KNOTS AND CHECKING DESIRABLE.	VERTICAL STOREFRONT APPLICATION		CLASS C FLAMESPREAD (175)
[WD-23a]	1/4" [6] THICK, SOLID STOCK WHITE OAK, TIGHT KNOTS DESIRABLE, SURFACED 4 SIDES, SANDED	STOREFRONT DOORS		CLASS C FLAMESPREAD (120)
[WD-24a]	WESTERN RED CEDAR, GRADE 'A' AND BETTER (WITHOUT KNOTS), FINISH S4S (SMOOTH 4 SIDES), NATURAL (NO TOPCOAT).	FITTING ROOMS		CLASS B FLAMESPREAD (70)
[WD-25a]	3/4" [19] 'RUSTIC OAK' (VENEERED) MEDIUM DENSITY FIBERBOARD (MDF) 5" [127] PLANKS (FIELD CUT AS REQUIRED)	FITTING ROOMS		CLASS C FLAMESPREAD (120)
[WD-26a]	1/4" [6] 'ARCHITECTURAL GRADE' (WHITE OAK VENEERED - TIGHT KNOTS AND CHECKING DESIRABLE) MEDIUM DENSITY FIBERBOARD (MDF) BY MILLWORK SUPPLIER.	F. ROOM MIRROR LOOSE TRIM FOR VISIBLE SIDE OF MIRROR & LIGHT BAR		CLASS C FLAMESPREAD (120)
[WD-27a]	1/2" [13] 'ARCHITECTURAL GRADE' (WHITE OAK VENEERED - TIGHT KNOTS AND CHECKING DESIRABLE) MEDIUM DENSITY FIBERBOARD (MDF) BY MILLWORK SUPPLIER	FITTING ROOM MIRROR FACE TRIM		CLASS C FLAMESPREAD (120)
[WD-28a]	1/2" [13] THICK, SOLID STOCK #2 COMMON PAINT GRADE YELLOW POPLAR AT WOOD DESIGNATED TO BE PAINTED, TIGHT KNOTS AND CHECKING DESIRABLE, SURFACED 2 SIDES, UNSANDED.	TRANSOM GLASS DIVIDER TRIM		CLASS C FLAMESPREAD (175)
[WD-29a]	1/2" [13] MEDIUM DENSITY FIBERBOARD (MDF) PREPRIMED.	PREFAB TRANSOM WINDOW COMPONENT		CLASS C FLAMESPREAD (120)

BASE MATERIAL

TYPE	DESCRIPTION	LOCATION	PROFILE	FLAME SPREAD
[B-1a]	3/4" [19] x 6" [152] SOLID STOCK #2 COMMON PAINT GRADE YELLOW POPLAR [WD-1a] FURNISHED BY TENANT, INSTALLED BY G.C.	SALES, VESTIBULE(S), FITTING ROOM(S) & PASSAGE AREAS		CLASS C FLAMESPREAD (175)
[B-2a]	1/4" [6] x 1 1/2" [38] SOLID STOCK WHITE OAK [WD-5a]. FURNISHED BY TENANT, INSTALLED BY G.C.	FREE STANDING DISPLAY CASES AS INDICATED		CLASS C FLAMESPREAD (175)
[B-3a]	4" [102] HIGH BLACK VINYL COVE BASE FURNISHED AND INSTALLED BY G.C.	STOCK ROOM, EGRESS CORRIDOR AND TOILET ROOM(S)		ASTM E 648 CLASS A FLAMESPREAD
[B-4a]	3/4" [19] x 3/4" [19] SOLID STOCK #2 COMMON PAINT GRADE YELLOW POPLAR [WD-1a] QUARTER ROUND BASE SHOE. FURNISHED BY TENANT, INSTALLED BY G.C.	BASE SHOE		CLASS C FLAMESPREAD (175)
[B-5a]	3/4" [19] x 5 1/2" [140] SOLID STOCK #2 COMMON PAINT GRADE YELLOW POPLAR [WD-1a] 1/4" CHAMFERED EDGE. FURNISHED BY TENANT, INSTALLED BY G.C.	SALES, VESTIBULE(S), FITTING ROOM(S) & PASSAGE AREAS		CLASS C FLAMESPREAD (175)
[B-6a]	3/4" [19] x 9" [229] SOLID STOCK #2 COMMON PAINT GRADE YELLOW POPLAR [WD-1a] 1/4" CHAMFERED EDGE. FURNISHED BY TENANT, INSTALLED BY G.C.	PILASTER(S), COLUMN(S) AS INDICATED		CLASS C FLAMESPREAD (175)
[B-7a]	3/4" [19] x 4" [102] SOLID STOCK #2 COMMON PAINT GRADE YELLOW POPLAR [WD-1a]. FURNISHED BY TENANT, INSTALLED BY G.C.	SALES, VESTIBULE(S), FITTING ROOM(S) & PASSAGE AREAS		CLASS C FLAMESPREAD (175)
[B-8a]	NOMINAL 24" [610] x 24" [610] 'SILVER LAKE' PORCELAIN TILE WITH 1/8" [3] WIDE SUMMITVILLE #562 NATURAL S-710 POLYCHROMES SANDED GROUT JOINTS. FURNISHED BY TENANT, INSTALLED BY G.C.	STOREFRONT		CLASS A FLAMESPREAD
[B-9a]	4" [102] HIGH WHITE, COMMERCIAL GRADE CERAMIC SANITARY COVE BASE WITH WHITE GROUT. FURNISHED AND INSTALLED BY G.C.	PUBLICLY ACCESSIBLE TOILET ROOM(S)		CLASS A FLAMESPREAD

SN#6258
"TRICORN BLACK"
= RAL 9011
= PANTONE 426C

FLOOR FINISHES

TYPE	DESCRIPTION	LOCATION	PROFILE	FLAME SPREAD
[FC-1a]	EXPOSED CONCRETE SLAB TO BE GROUND & POLISHED BY G.C. - SEE SPECIFICATIONS ON SHEET 'A.O.030' - COORDINATE WITH TENANT FIELD REP.	AS INDICATED (SEE FLOOR FINISH PLAN)		
[FC-2a]	EXPOSED CONCRETE/PLYWOOD - PAINT [P-6a]	STOCK ROOM, EGRESS CORRIDOR		
[FC-3a]	VENEERED LAMINATE FLOOR SYSTEM (4" [127] KULTUR, SUNSET MAPLE ECO-CLIQUE - 30% SHEEN) (PREFINISHED) GLED TO SLAB. FURNISHED AND INSTALLED BY TENANT, G.C. SHALL COORDINATE.	SALES AREA AS INDICATED		ASTM E 648 CLASS A FLAMESPREAD
[FC-4a]	EXPOSED CONCRETE SLAB TO BE GROUND & POLISHED BY G.C. - SEE SPECIFICATIONS ON SHEET 'A.O.030' - COORDINATE WITH TENANT FIELD REP.	SALES AREA AS INDICATED		ASTM E 648 CLASS A FLAMESPREAD
[FC-5a]	NOMINAL 16" [406] x 32" [813] 'SILVER LAKE' PORCELAIN TILE WITH 1/8" [3] WIDE SUMMITVILLE #562 NATURAL S-710 POLYCHROMES SANDED GROUT JOINTS. FURNISHED BY TENANT, INSTALLED BY G.C.	SALES AREA		CLASS A FLAMESPREAD
[FC-6a]	NOMINAL 24" [610] x 24" [610] 'SILVER LAKE' PORCELAIN TILE WITH 1/8" [3] WIDE SUMMITVILLE #562 NATURAL S-710 POLYCHROMES SANDED GROUT JOINTS. FURNISHED BY TENANT, INSTALLED BY G.C.	STOREFRONT		CLASS A FLAMESPREAD
[FC-7a]	COMMERCIAL GRADE SHEET VINYL 'WHITE' OVER WATERPROOF MEMBRANE FURNISHED AND INSTALLED BY G.C.	TOILET ROOM(S)		ASTM E 648 CLASS A FLAMESPREAD
[FC-8a]	NOMINAL 16" [406] x 32" [813] 'ASH GREY MATTE' PORCELAIN TILE WITH 1/8" [3] WIDE SANDED GROUT JOINTS LATICRETE #78 STERLING GRAY, FURNISHED BY TENANT, INSTALLED BY G.C.	SALES AREA		CLASS A FLAMESPREAD
[FC-9a]	NOMINAL 24" [610] x 24" [610] 'CLAY - OLIVE' PORCELAIN TILE WITH 1/8" [3] WIDE SUMMITVILLE #526 'TAUPE' S-710 POLYCHROMES SANDED GROUT JOINTS. FURNISHED BY TENANT, INSTALLED BY G.C.	SALES AREA		CLASS A FLAMESPREAD
[FC-10a]	VENEERED FLOOR SYSTEM (6" [152] KEMPER ECKLIK+ BRUSHED, PREFINISHED FRENCH WHITE OAK 10% SHEEN) GLED TO SLAB. RESANDABLE 2-3 TIMES. FURN. BY TENANT, INST. BY G.C. (MANUFACTURED EXCLUSIVELY FOR AEO)	AS INDICATED (SEE FLOOR FINISH PLAN)		ASTM E 648 CLASS A FLAMESPREAD
[FC-11a]	17 1/2" [443] x 17 1/2" [443] 'PENNSYLVANIA BLUE STONE' (RUNNING BOND) TILE WITH 1/2" [13] WIDE SUMMITVILLE #571 'SMOKE' S-710 POLYCHROMES SANDED GROUT JOINTS. FURNISHED BY TENANT, INSTALLED BY G.C.	SALES AREA		CLASS A FLAMESPREAD
[FC-12a]	SUPERNOB 52 TILE ENTRY MAT - 19-11/16" x 19-11/16" TILES - ZINC. FURNISHED BY TENANT, INSTALLED BY G.C. PER MANUFACTURER RECOMMENDATION. TILES TO BE INSTALLED IN 1/4 TURN PATTERN	SALES AREA ENTRY		

NOTE: G.C. SHALL APPLY 'TRUSTY-STEP' ANTI-SLIP FLOOR TREATMENT TO ALL NON-'BLUE STONE' EXTERIOR TILE (SCOF = .8 WET AND DRY)

METAL FINISHES

TYPE	DESCRIPTION	LOCATION	PROFILE	FLAME SPREAD
[M-1a]	HOT-ROLLED STEEL (MILL FINISH) CLEAN GROUND WELDS, NO HEAT MARKS, CLEAR MATTE POWDER COAT - TIGER 016-00393	INTERIOR METALS AS INDICATED	PROFILE VARIES	CLASS A FLAMESPREAD
[M-2a]	BRUSHED COLD ROLLED STEEL 180 GRIT LINEAR BRUSHING, NO HEAT MARKS, CLEAN GROUND WELDS	INTERIOR METALS AS INDICATED	PROFILE VARIES	CLASS A FLAMESPREAD
[M-3a]	COLD ROLLED STEEL 80 GRIT 'DUAL ACTION' ORBITAL SANDING, NO HEAT MARKS, CLEAN GROUND WELDS	INTERIOR METALS AS INDICATED	PROFILE VARIES	CLASS A FLAMESPREAD
[M-4a]	ALUMINUM PREFINISHED WITH STEEL METALLIC - PPS 3041 POWDER COAT FINISH FROM PERFORMANCE POWDERS	EXTERIOR/INTERIOR METALS AS INDICATED	PROFILE VARIES	CLASS A FLAMESPREAD
[M-5a]	ALUMINUM WITH 80 GRIT 'DUAL ACTION' ORBITAL SANDING, NO HEAT MARKS, CLEAN GROUND WELDS (CLEAR COAT)	EXTERIOR METALS AS INDICATED	PROFILE VARIES	CLASS A FLAMESPREAD
[M-6a]	3/4" [19] x 3/4" [19] ALUMINUM REVEAL BLACK FINISH - FURNISHED AND INSTALLED BY G.C. (BLIND FASTENED)	STOREFRONT		CLASS A FLAMESPREAD
[M-7a]	WEATHERED ZINC TO MIMIC GALVANIZED FINISH	FITTING ROOMS AS INDICATED	PROFILE VARIES	CLASS A FLAMESPREAD

STAIN FINISHES

TYPE	DESCRIPTION	LOCATION	APPLICATION
[ST-1a]	CORONADO AQUA-PLASTIC URETHANE 70-200 CLEAR DULL	LIGHT STAINED WOOD AS INDICATED	ONE (1) COAT, SPRAY APPLIED OVER LIGHTLY SANDED MATERIAL
[ST-2a]	CHEMCRAFT L70434 HICKORY DARK STAIN (CUT BY 50%)	MEDIUM STAINED WOOD AS INDICATED	ONE (1) COAT, WIPE ON, FOLLOWED BY [ST-1a]

CEILING FINISHES

TYPE	DESCRIPTION	LOCATION	PROFILE	FLAME SPREAD
[CT-1a]	USG 'ECLIPSE' CLIMAPLUS FIRECODE 2'x2' REGULAR EDGE ACOUSTICAL TILE #76979, COLOR WHITE. USE DOWN CENTRIC 12" DIAL SERIES NARROW PROFILE GRID, COLOR FLAT WHITE. NO SUBSTITUTIONS. USG STRATEGIC ACCOUNT QUOTE #E014019. CONTACT USG CUSTOMER SERVICE AT 1-800-850-3839 WITH QUESTIONS.	SALES, VESTIBULE, FITTING ROOM(S) & PASSAGE AREAS		CLASS A FLAMESPREAD
[CT-2a]	USG 'FIGURED' FIRECODE 2'x4' SQUARE EDGE ACOUSTICAL TILE #586, COLOR WHITE. USE DOWN DXL SERIES STANDARD PROFILE GRID, COLOR FLAT WHITE.	STOCK ROOM		CLASS A FLAMESPREAD

MASONRY FINISHES

TYPE	DESCRIPTION	LOCATION	PROFILE	FLAME SPREAD
[T-1a]	6" [152] x 12" [305] WHITE COMMERCIAL GRADE CERAMIC SUBWAY TILE WITH 'MAPEI' 09 GRAY MODIFIED SANDED GROUT (3/16" [5] JOINTS). FURNISHED BY TENANT, INSTALLED BY G.C.	DISPLAY AREA WALLS, STOREFRONT		CLASS A FLAMESPREAD
[T-2a]	4" [102] x 4" [102] WHITE, COMMERCIAL GRADE CERAMIC TILE WITH WHITE GROUT. FURNISHED AND INSTALLED BY G.C.	TOILET ROOM APPLICATIONS AS INDICATED		CLASS A FLAMESPREAD
[BR-1a]	INDIVIDUAL BRICK PIECES APPLIED TO DRYWALL OR PLYWOOD SUBSTRATE WITH LATICRETE HEAVY DUTY THINSET. 3/8" MORTAR JOINTS, APPLY MORTAR WITH TILE FLOAT. ALLOW TO DRY A BIT, USE STIFF BRUSH TO KNOCK LOOSE MORTAR FROM BRICK. ENDICOTT 'AEO SANDS'	STOREFRONT, INTERIOR COLUMN & WALL APPLICATIONS AS INDICATED		CLASS A FLAMESPREAD
[BR-2a]	INDIVIDUAL BRICK PIECES APPLIED TO DRYWALL OR PLYWOOD SUBSTRATE WITH LATICRETE HEAVY DUTY THINSET. 3/8" THUMB STRUCK MORTAR JOINTS. ENDICOTT 'MANGANESE IRONSPOT', SMOOTH TEXTURE, OR APPROVED EQUAL. G.C. SHALL NOT OVERSTRIKE MORTAR JOINTS.	SPECIAL STOREFRONT APPLICATIONS AS INDICATED		CLASS A FLAMESPREAD
[PL-1a]	G.C. SHALL APPLY (1) COAT [P-20a] TO SURFACE. G.C. SHALL SPRAY APPLY SHERWIN WILLIAMS ULTRACRETE (TEXTURED MASONRY TOPCOAT) FINE #A444#800. FINISH WITH (2) COATS [P-8a]	STOREFRONT PLASTER FINISH APPLICATIONS		CLASS A FLAMESPREAD
[PL-2a]	8" [203] BOARD-FORMED CONCRETE OVER 5/8" [16] PLYWOOD	STOREFRONT CONCRETE FINISH APPLICATIONS		CLASS A FLAMESPREAD

GLASS MATERIAL

TYPE	DESCRIPTION	LOCATION	PROFILE	FLAME SPREAD
[GL-1a]	3/8" [19] CLEAR TEMPERED SAFETY STOREFRONT GLASS	STOREFRONT GLASS		CLASS A FLAMESPREAD
[GL-2a]	1/4" [6] POLISHED PLATE GLASS MIRROR.	MIRROR(S)		CLASS A FLAMESPREAD
[GL-3a]	1/4" [6] CLEAR TEMPERED GLASS	TRANSOM GLASS AS INDICATED		CLASS A FLAMESPREAD
[GL-4a]	1/4" [6] TEMPERED FROSTED GLASS, 'FROST ETCH 100' AS MANUFACTURED BY ARCH DECO GLASS 1-800-870-2519 (NO SUBSTITUTIONS)	TRANSOM GLASS AS INDICATED		CLASS A FLAMESPREAD
[GL-5a]	1/4" [6] POLISHED PLATE WIRE GLASS MIRROR (ORIENTED 45°)	DOOR MIRROR(S)		CLASS A FLAMESPREAD
[GL-6a]	1/2" [13] FROSTED TEMPERED SAFETY STOREFRONT GLASS, 'FROST ETCH 100' AS MANUFACTURED BY ARCH DECO GLASS 1-800-870-2519 (NO SUBSTITUTIONS)	STOREFRONT GLASS		CLASS A FLAMESPREAD
[GL-7a]	1" [25] INSULATED CLEAR TEMPERED SAFETY STOREFRONT GLASS	STOREFRONT GLASS		CLASS A FLAMESPREAD
[GL-8a]	1/4" [6] TEMPERED WIRE GLASS (ORIENTED 45°)	DOORS		CLASS A FLAMESPREAD
[GL-9a]	1/4" HAMMERED WIRE GLASS (ORIENTED 45°), FROSTED (SANDBLASTED) ON HAMMERED SIDE. GLASS TO BE INSTALLED SMOOTH SIDE OUT, FOR STENCILING.	DOORS		CLASS A FLAMESPREAD
[GL-10a]	3/16" HAMMERED, FROSTED GLASS. PATTERN 62 OBSCURE, TEMPERED. LLUMAR WHITE ETCH FROST PRIVACY FILM ON SMOOTH SIDE. #NRYV60FP53	DOORS & TRANSOMS		CLASS A FLAMESPREAD

PAINT FINISHES

TYPE	DESCRIPTION	LOCATION	APPLICATION
[P-1a]	SHERWIN WILLIAMS PROMAR 200 ZERO VOC INTERIOR LATEX SEMI-GLOSS (B31W265) SERIES) SN#7006 'EXTRA WHITE'	WOOD, TRIM AND DOORS	TWO (2) COATS, BRUSH OR SPRAY THEN BACK BRUSH, OVER [P-50a]
[P-2a]	SHERWIN WILLIAMS PROMAR 200 ZERO VOC INTERIOR LATEX SEMI-GLOSS (B31W265) SERIES) SN#7006 'EXTRA WHITE'	AS INDICATED	TWO (2) COATS, SPRAY THEN BACK ROLL, OVER [P-51a]
[P-3a]	SHERWIN WILLIAMS PROMAR 200 ZERO VOC INTERIOR LATEX FLAT (B30W2650 SERIES) SN#7006 'EXTRA WHITE'	DRYWALL CEILING	TWO (2) COATS, SPRAY THEN BACK ROLL, OVER [P-51a]
[P-4a]	SHERWIN WILLIAMS PROMAR 200 ZERO VOC INTERIOR LATEX SEMI-GLOSS (B31W2654 SERIES) SN#7006 'BLACK MAGIC'	WOOD TRANSOMS	TWO (2) COATS, BRUSH OR SPRAY THEN BACK BRUSH, OVER [P-50a]
[P-5a]	SHERWIN WILLIAMS PROMAR 200 ZERO VOC INTERIOR LATEX EG-SHEL (B20W2651 SERIES) SN#7066 'GRAY MATTERS'	OPEN CEILING	TWO (2) COATS, SPRAY APPLIED OVER [P-50a]
[P-6a]	SHERWIN WILLIAMS ARMORSEAL FLOOR-PLEX 7100 WATER BASED EPOXY FLOOR COATING #B70A400 'HAZE GRAY'	STOCK ROOM, EGRESS CORRIDOR FLOOR	TWO (2) COATS, ROLLED, OVER [P-52a]
[P-7a]	SHERWIN WILLIAMS PROMAR 200 ZERO VOC INTERIOR LATEX EG-SHEL (B20W2651 SERIES) SN#7064 'IRON ORE'	STAIR STRUCTURE & RELATED COMPONENTS (AS INDICATED)	TWO (2) COATS, SPRAY APPLIED OVER [P-50a]
[P-8a]	SHERWIN WILLIAMS SUPERPAINT EXTERIOR LATEX SATIN SUPER WHITE (A89W16)	EXTERIOR WALLS	TWO (2) COATS, BRUSH OR SPRAY THEN BACK BRUSH, OVER [P-50a]
[P-9a]	PAINT TO MATCH COLD ROLLED STEEL - CONTACT DSI @ 1-800-745-1778 WOOD PRIMER = DSI #22CSA4600-1G TATICA SILVER CLANLOCK PRIMER WOOD PAINT = DSI #22CSA4600-1G TATICA SILVER MAX SATIN	LIGHT BAR	TWO (2) COATS, SPRAY APPLIED OVER [P-50a]
[P-10a]	SHERWIN WILLIAMS PROMAR 200 ZERO VOC INTERIOR LATEX EG-SHEL (B20W2654 SERIES) SN#7048 'URBANE BRONZE'	STOREFRONT LID	TWO (2) COATS, SPRAY THEN BACK ROLL, OVER [P-51a]
[P-11a]	SHERWIN WILLIAMS PROMAR 200 ZERO VOC INTERIOR LATEX SEMI-GLOSS (B31W265) SERIES) SN#6126 'NAVAJO WHITE'	CEILING BEAM(S)	TWO (2) COATS, SPRAY THEN BACK ROLL, OVER [P-51a]
[P-12a]	SHERWIN WILLIAMS PROMAR 200 ZERO VOC INTERIOR LATEX SEMI-GLOSS (B31W265) SERIES) SN#6126 'NAVAJO WHITE'	WOOD MATERIAL	TWO (2) COATS, BRUSH OR SPRAY THEN BACK BRUSH, OVER [P-50a]
[P-13a]	SHERWIN WILLIAMS PROMAR 200 ZERO VOC INTERIOR LATEX EG-SHEL (B20W2651 SERIES) SN#6258 'TRICORN BLACK'	AS INDICATED	TWO (2) COATS, SPR